



Battery pack

LS-24V100Ah



Specification

Parameter	Characteristic
Cell Type	LP2770120(8S6P)
Nominal Module Voltage	25.6 V
Nominal Capacity	100 Ah
Dimensions	386(L) x 330(W) x 145(H)(mm)
Weight	24 kg
Terminal Female-Threaded	M6x1.25
Specific Energy	106 Wh/kg
Energy Density	138 Wh/L
Discharge temperature	-20°C~50°C
Charge temperature	0°C~45°C
Storage temperature	-20°C~50°C
Water/dust resistance	-
Certification	SAE J 2464, CE
Shipping Classification	UN38.3

Overview

LS series is a family of 12 V, 24 V battery pack. LS-24V100Ah is in this series.

LS-24V100Ah is high specific energy, short-time charging, high safety and reliability.

Features

- Compact size
- Much lighter weight similar sized lead-acid batteries
- Extraordinary cycle life ->2000 cycles at 80%DOD.
- Maintenance free
- Rugged mechanical design
- Flame retardant plastics
- Inter module balancing

This document represents typical data. Performance may vary depending on use conditions and application.

AX Power Solution GmbH makes no warranty explicit or implied with this data sheet. Contents subject to change without notice.

AX Power Solution GmbH

Hanauer Landstraße 291 A
D-60314 Frankfurt am Main

Tel: 069 - 3660 5813
Fax: 069 - 2729 2921

