

High Power Lithium-Ion Cell

LP2714897AE

1. Scope




LISHEN High Power Cells are 100% automatically manufactured and produced under the strict quality control to ensure long life, secure usage and very high performance. To be able to combine cells in systems, our products are automatically sorted under the strongest restrictions to optimise performance of cell blocks and systems as well as to reduce cost for electronic balancing systems.

2. Description and Model

LISHEN High Power Cells find their applications in all kind of mobile transport application, such as fork lifts, e-scooters, e-cars, e-busses as well as storage applications for small and high volume storage systems.


3. Specifications

Item	Specification
Nominal Capacity	28 Ah
Nominal Voltage	3.65 V
AC-impedance	$\leq 1.5 \text{ m}\Omega$
charge	
- Standard Charge Method	CC/CV
- Current	1/3 C
- Voltage	4.2 V
- End Current	1.4 A
- Maximum charge current	200 A, 240 A (10 s)
discharge	
- Standard Discharge Method	Constant Current (CC)
- Current	1 C
- End Voltage	2.8 V
- Maximum Discharge Current	200 A, 320 A (10 s)
Size	26.5 mm T, 148 mm W, 96.5 mm H
Cycle Life	2000Cycles at 80% DoD 3.000 cycles at 70% DoD
Weight	725 \pm 10 g
Maximum Operating Temperature Range	0°C ~ 45°C, charge -20°C ~ 60°C, discharge
Storage Temperature	-40°C ~ 45°C, one month / -20°C ~ 60°C, six months
Chemie	Lithium Eisenphosphat, LiFePO4



High Power Lithium-Ion Cell

LP2714897AE



Applications

COMMERCIAL SOLUTIONS

- UPS Datacenter
- Telecom and IT backup
- Industrial material handling equipment

GOVERNMENT SOLUTIONS

- Military vehicles
- Military power grids
- GRID SOLUTIONS
- Frequency regulation
- Renewables storage integration
- Reserve capacity

TRANSPORTATION SOLUTIONS

Hybrid, plug-in hybrid and electric vehicle battery systems for:

- Commercial vehicles
- Off-highway vehicles
- Passenger vehicles

This document represents typical data. Performance may vary depending on use conditions and application.

AX Power Solution GmbH makes no warranty explicit or implied with this data sheet. Contents subject to change without notice.

AX Power Solution GmbH

Hanauer Landstraße 291 A
D-60314 Frankfurt / Main

Tel: 069 - 3660 5813
Fax: 069 - 2729 2921

